

Cyclic Load Energy Saver



MODEL : LEDXT-DSM

7 Segment LED /6 Digit Display

Protection

Over Load
Single Phasing
Unbalance
Under Current
Lock Rotor
Short Circuit
Earth Leakage (*Extra CBCT Required*)

Features

3Ph Current Display
Fault Annunciation
Last 5 Fault History FIFO based
Reset Inhibit Function
Automatic Delta Star Converter
Energy Saver
IT- Characteristic
Bypass through manual mode
230VAC, 50 Hz
Dimension : 96x96 mm, Flush Mounting

Description

Cat. No.

Unit Rate [Rs.]

Range : 0.8 - 25 Amp, Line CT -03 Nos. ID - 20mm	LEDXT-DSM - 0.8-25A	On Request
Range : 2 - 62.5 Amp, Line CT -03 Nos. ID - 20mm	LEDXT-DSM - 2-62.5A	On Request
Range : 4 - 125 Amp, Line CT -03 Nos. ID - 35mm	LEDXT-DSM - 4-125A	On Request
Range : 40 - 250 Amp, Line CT -03 Nos. ID - 55mm	LEDXT-DSM - 40-250A	On Request
Range : 80 - 500 Amp, Line CT -03 Nos. ID - 55mm	LEDXT-DSM - 80-500A	On Request

HSN Code : 8536

GST : 18% Exclusive



Cameosys Pvt. Ltd.

Email:cameosys11@gmail.com
cameosys21@gmail.com
Mobile : +91 99790 41111