

# Motor Protection Relay



MODEL : D-LEDXT

Din Rail Mountable

7 Segment LED/4 Digit Display

## Protection

Over Load  
Single Phase  
Unbalance  
Under Current  
Lock Rotor  
Short Circuit  
Earth Fault \*(*Extra CBCT Required*)

## Features

3 Ph Current Display  
Fault Annunciation  
Last 5 Fault History FIFO Based  
I-T Characteristic  
Dimension : 110x100x75 mm, Din Rail Mounting

| Description  | Cat. No.            | Unit Rate [Rs.] |
|--|---------------------|-----------------|
| Range : 0.2 - 6.25 Amp, Line CT -03 Nos. ID - 15mm (Inbuilt) | D-LEDXT - 0.2-6.25A | On Request      |
| Range : 0.4 - 12.5 Amp, Line CT -03 Nos. ID - 15mm (Inbuilt) | D-LEDXT - 0.4-12.5A | On Request      |
| Range : 0.8 - 25 Amp, Line CT -03 Nos. ID - 15mm (Inbuilt)   | D-LEDXT - 0.8-25A   | On Request      |
| Range : 2 - 62.5 Amp, Line CT -03 Nos. ID - 15mm (Inbuilt)   | D-LEDXT - 2-62.5A   | On Request      |
| Range : 4 - 125 Amp, Line CT -03 Nos. ID - 35mm              | D-LEDXT - 4-125A    | On Request      |
| Range : 40 - 250 Amp, Line CT -03 Nos. ID - 55mm             | D-LEDXT - 40-250A   | On Request      |
| Range : 80 - 500 Amp, Line CT -03 Nos. ID - 55mm             | D-LEDXT - 80-500A   | On Request      |

**Aux. Supply :** 230VAC, 50 Hz ( *Optional 110VAC / 415VAC*) Kindly Mention in Purchase Order

## Optional :

RS- 485 Communication Modbus Protocol  
Analog O/P (4-20mA/ 0-10VDC)  
Extra Relay Output  
Password Protection

HSN Code : 85364900

GST : 18% Exclusive



**Cameosys Pvt. Ltd.**

Email:cameosys11@gmail.com  
cameosys21@gmail.com  
Mobile : +91 99790 41111