

Motor Protection Relay



MODEL : μDTB-LEDXT

Detachable console

7 Segment LED/4 Digit Display

Protection

Over Load
Single Phasing
Unbalance
Under Current
Lock Rotor
Short Circuit
Earth Fault *(Extra CBCT Required)

Features

3Ph Current Display
Fault Annunciation
Last 5 Fault History FIFO based
I-T Characteristic
Din Rail Mounting
Dimension : 110 x 100 mm (Basic Relay),
: 48x96 mm (DTC Console)

Description

Cat. No.

Unit Rate [Rs.]

Range : 0.2 - 6.25 Amp, Line CT -03 Nos. ID - 15mm (Inbuilt)	DTB-LEDXT - 0.2-6.25A	On Request
Range : 0.4 - 12.5 Amp, Line CT -03 Nos. ID - 15mm(Inbuilt)	DTB-LEDXT - 0.4-12.5A	On Request
Range : 0.8 - 25 Amp, Line CT -03 Nos. ID - 15mm (Inbuilt)	DTB-LEDXT - 0.8-25A	On Request
Range : 2 - 62.5 Amp, Line CT -03 Nos. ID - 15 mm (Inbuilt)	DTB-LEDXT - 2-62.5A	On Request
Range : 4 - 125 Amp, Line CT -03 Nos. ID - 35mm	DTB-LEDXT - 4-125A	On Request
Range : 40 - 250 Amp, Line CT -03 Nos. ID - 55mm	DTB-LEDXT - 40-250A	On Request
Range : 80 - 500 Amp, Line CT -03 Nos. ID - 55mm*	DTB-LEDXT - 80-500A*	On Request

* without Short Circuit Protection

Aux. Supply : 230VAC, 50 Hz (Optional 110VAC / 415VAC) Kindly Mention in Purchase Order

Optional :

RS- 485 Communication Modbus Protocol

Analog O/P (4-20mA/ 0-10VDC)

Extra Relay Output

Password Protection

HSN Code : 85364900

GST : 18% Exclusive



Cameosys Pvt. Ltd.

Email:cameosys11@gmail.com

cameosys21@gmail.com

Mobile : +91 99790 41111