



Earthing Relay

MODEL : ECR - 1- D

Earthing Confirmation System with Display

Application

Tankers loading - Unloading
Process Equipment : Reactor & Vessels
Intrinsically Safe Earthing Confirmation Relay

Technical Specification

Inputs

1. True-Earth point at loading area
2. Probe from body of an earthed Truck

Outputs

Two Relay change-over (potential -free)
5 Amps @ 230VAC (Resistive Load)

Range

8 Ohms. (Earth Loop Resistance upto 10 Ohms adjustable)

Indication

Green LED indicating successful grounding (EARTH OK)
Red LED for POWER ON or EARTH OPEN

Power Supply

230 V AC , 50 Hz ($\pm 10\%$)

Set Comprising of...

Earthing Relay in FLP Enclosure
with SS Clamp having 5 meter Cable - 02 Nos.

Description	Cat. No.	Unit Rate [Rs.]
ECR-1-D with Display (CMRI Approved)	ECR - 1 - D	On Request
ECR-1-D with Display (PESO Approved)	ECR - 1 - D	On Request

Note : For Other Approval or Certification - Price on Request

Optional :

Certified Intrinsically safe barrier
Earth Fail Indication

HSN Code : 8536

GST : 18% Exclusive



Cameosys Pvt. Ltd.

Email:cameosys11@gmail.com
cameosys21@gmail.com
Mobile : +91 99790 41111