



Motor Protection Relay

MODEL : eLEDX-T

7 Segment LED/ 6 Digit Display

Protection

Over Load
Single Phasing
Unbalance
Under Current
Lock Rotor
Short Circuit
High Voltage
Low Voltage
Earth Fault *(Extra CBCT Required)

Features

A, V, KW, Kwh & PF Display
Hour Counter
Start Counter
RS - 485 Communication Modbus Protocol
I-T Characteristic
Fault Annunciation display type of fault
Last 5 Fault History FIFO based
Dimension: 96 x 96 mm, Flush Mounting

Description

Cat. No.

Unit Rate [Rs.]

Range : 0.2 - 12.5 Amp, Line CT -03 Nos. ID - 20mm	eLEDXT - 0.2-12.5A	On Request
Range : 0.8 - 25 Amp, Line CT -03 Nos. ID - 20mm	eLEDXT - 0.8-25A	On Request
Range : 2 - 62.5 Amp, Line CT -03 Nos. ID - 20mm	eLEDXT - 2-62.5A	On Request
Range : 4 - 125 Amp, Line CT -03 Nos. ID - 35mm	eLEDXT - 4-125A	On Request
Range : 40 - 250 Amp, Line CT -03 Nos. ID - 55mm	eLEDXT - 40-250A	On Request
Range : 80 - 500 Amp, Line CT -03 Nos. ID - 55mm* * without Short Circuit Protection	eLEDXT - 80-500A*	On Request

Aux. Supply : 230VAC, 50 Hz (Optional 110VAC / 415VAC) Kindly Mention in Purchase Order

Optional :

Analog O/P (4-20mA/ 0-10VDC)
Password Protection
RTC
Extra Relay Output

HSN Code : 85364900

GST : 18% Exclusive



Cameosys Pvt. Ltd.

Email:cameosys11@gmail.com
cameosys21@gmail.com
Mobile : +91 99790 41111