



Motor Protection Relay

MODEL : μLEDX-T

7 Segment LED/4 Digit Display

Protection

Over Load
Single Phasing
Unbalance
Under Current
Lock Rotor
Short Circuit
Earth Leakage (*Extra CBCT Required*)

Features

3Ph Current Display
Run Hour
Start Counter
Fault Annunciation
Last 5 Fault History FIFO based
Reset Inhibit Function
I-T Characteristic
Dimension : 96 x 96 mm, Flush Mounting

Description

Cat. No.

Unit Rate [Rs.]

Range : 0.2 - 6.25 Amp, Line CT -03 Nos. ID - 20mm	LEDXT - 0.2-6.25A	On Request
Range : 0.4 - 12.5 Amp, Line CT -03 Nos. ID - 20mm	LEDXT - 0.4-12.5A	On Request
Range : 0.8 - 25 Amp, Line CT -03 Nos. ID - 20mm	LEDXT - 0.8-25A	On Request
Range : 2 - 62.5 Amp, Line CT -03 Nos. ID - 20mm	LEDXT - 2-62.5A	On Request
Range : 4 - 125 Amp, Line CT -03 Nos. ID - 35mm	LEDXT - 4-125A	On Request
Range : 40 - 250 Amp, Line CT -03 Nos. ID - 55mm	LEDXT - 40-250A	On Request
Range : 80 - 500 Amp, Line CT -03 Nos. ID - 55mm* <i>* without Short Circuit Protection</i>	LEDXT - 80-500A*	On Request
Range : 100-1000 Amp, Line CT -03 Nos. ID - 80mm	HLEDXT - 100-1000A	On Request

Aux. Supply : 230VAC, 50 Hz (Optional 110VAC / 415VAC) Kindly Mention in Purchase Order

Optional :

RTC (Real Time Clock)
RS- 485 Communication Modbus Protocol
Analog O/P (4-20mA/ 0-10VDC)
Extra Relay Output
Thermistor Protection/Phase Reversal
Password Protection

HSN Code : 85364900

GST : 18% Exclusive



Cameosys Pvt. Ltd.

Email:cameosys11@gmail.com
cameosys21@gmail.com
Mobile : +91 99790 41111